




carbon steel parallel Metric thread 24° compression fitting swivel union



24° compression fitting according to **DIN 3865 form B**

**Material:** Carbon Steel

**Finish:** Zinc-plated

Ø tube	dimensions								working pressure	ISO series
	L1	H2				m	O-ring	MPa		
6	37	14				12x1,5	4x1,5	31.5	L	
8	37	17				14x1,5	6x1,5	31.5	L	
10	38	19				16x1,5	7,5x1,5	31.5	L	
12	38	22				18x1,5	9x1,5	31.5	L	
15	42	27				22x1,5	12x2	31.5	L	
18	40	32				26x1,5	15x2	31.5	L	
22	47	36				30x2	20x2	16.0	L	
28	48	41				36x2	26x2	16.0	L	
35	56	50				45x2	32x2,5	16.0	L	
42	56	60				52x2	38x2,5	16.0	L	
6	38	17				14x1,5	4x1,5	63.0	S	
8	38	19				16x1,5	6x1,5	63.0	S	
10	41	22				18x1,5	7,5x1,5	63.0	S	
12	42	24				20x1,5	9x1,5	63.0	S	
14	45	27				22x1,5	10x2	63.0	S	
16	47	30				24x1,5	12x2	40.0	S	
20	55	36				30x2	16,3x2,4	40.0	S	
25	59	46				36x2	20,3x2,4	40.0	S	
30	62	50				42x2	25,3x2,4	40.0	S	
38	67	60				52x2	33,3x2,4	31.5	S	

also available:

### Stainless Steel 24° Compression Ring

(add an 'S' at the end of the part number; ex: 34.635.12S)