



EPDM Rubber Sheet

EPDM rubber sheet black color with no insertion and with one or two insertions



- Raw Material:** black EPDM
- Reinforcement:** 0, 1 or 2 insertions
- Hardness:** 65 ± 5 Shore A
- Tensile strength:** 4.0 MPa
- Elongation:** 250%
- Temperature:** - 40°C to + 100°C (-40°F to 212°F)
- Specific Gravity:** 1.5g / cm³
- Weather resistance:** good resistance
- UV resistance:** good resistance
- Oil resistance:** non resistant
- Gasoline and fuel resistance:** non resistant
- Acid and solvents resistance:** non resistant
- Abrasion resistance:** moderate resistance
- Strong bases:** moderate resistance
- Impact resistance:** resistant

Thickness		Width		Length		Nr. of insertions
mm	inch	m	feet	m	feet	
0,8	1/32"	1,22	4.0	10	32.81	0
1,6	1/16"	1,22	4.0	10	32.81	0
3,2	1/8"	1,22	4.0	10	32.81	0
4,8	3/16"	1,22	4.0	10	32.81	0
6,4	1/4"	1,22	4.0	10	32.81	0
7,9	5/16"	1,22	4.0	10	32.81	0
9,5	3/8"	1,22	4.0	10	32.81	0
12,7	1/2"	1,22	4.0	10	32.81	0

Thickness		Width		Length		Nr. of insertions
mm	inch	m	feet	m	feet	
1,6	1/16"	1,22	4.0	10	32.81	1
3,2	1/8"	1,22	4.0	10	32.81	1
4,8	3/16"	1,22	4.0	10	32.81	1
6,4	1/4"	1,22	4.0	10	32.81	1

Thickness		Width		Length		Nr. of insertions
mm	inch	m	feet	m	feet	
3,2	1/8"	1,22	4.0	10	32.81	2
4,8	3/16"	1,22	4.0	10	32.81	2
6,4	1/4"	1,22	4.0	10	32.81	2

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.