



WATER DISCHARGE HOSE || MANGUERA DE DESCARGA DE AGUA



Application

Designed for water and non-corrosive fluids used in construction sites and light duty industrial applications.

Tube

Black, smooth, synthetic rubber.

Reinforcement

High strength synthetic cord.

Cover

Black, smooth, synthetic rubber, weathering and ozone resistant.

Temperature Range

-40°C (-40°F) +70°C (+158°F)

Aplicación

Diseñado para agua y fluidos no corrosivos utilizados en obras de construcción y aplicaciones industriales ligeras.

Tubo interior

Negro, liso, caucho sintético.

Refuerzo

cuerda sintética de alta resistencia

Cubierta exterior

Negro, liso, caucho sintético, resistente a la intemperie y resistente al ozono.

Temperatura -40°C (-40°F) +70°C (+158°F)

Item Code.	ID		OD	WP		BP		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
WDH-04	3/16"	4.8	12	10	150	30	450	120	400
WDH-06	1/4"	6.4	13	10	150	30	450	120	400
WDH-07	5/16"	7.9	15	10	150	30	450	100	330
WDH-09	3/8"	9.5	16	10	150	30	450	100	330
WDH-12	1/2"	12.7	20	10	150	30	450	100	330
WDH-15	5/8"	15.9	23.5	10	150	30	450	100	330
WDH-19	3/4"	19.1	27	10	150	30	450	100	330
WDH-22	7/8"	22.2	30	10	150	30	450	100	330
WDH-25	1"	25.4	34	10	150	30	450	100	330
WDH-31	1-1/4"	31.8	42	10	150	30	450	60	200
WDH-38	1-1/2"	38.1	48	10	150	30	450	60	200
WDH-50	2"	50.8	62	10	150	30	450	60	200
WDH-63	2-1/2"	63.5	76	10	150	30	450	60	200
WDH-76	3"	76.2	89	10	150	30	450	60	200
WDH-88	3-1/2"	88.9	103	10	150	30	450	60	200
WDH-101	4"	101.6	116	10	150	30	450	60	200
WDH-127	5"	127	142	10	150	30	450	30	100
WDH-152	6"	152.4	167	10	150	30	450	30	100
WDH-203	8"	203.2	219	10	150	30	450	30	100