



MULTIPURPOSE OIL, FUEL & GASOLINE

Oil, Fuel and Gasoline 2.0MPa / 300PSI (100% rubber hose)



- Inner tube:** seamless oil, fuel and gasoline resistant synthetic rubber
Reinforcement: 1 high resistance synthetic fiber braid
Outer tube: black wrapped, weather and abrasion resistant synthetic rubber
Safety factor: 3: 1
Application: oil, fuel and gasoline on automotive, and service stations
Temperature range: - 40°C (- 40°F) + 100°C (+ 212°F)

Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
		mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	
3/16"	- 3	4,8	0.19	11,1	0.44	2.0	300	6.0	900	50	2.0	0,10
1/4"	- 4	6,4	0.25	14,0	0.55	2.0	300	6.0	900	60	2.4	0,12
5/16"	- 5	7,9	0.31	15,5	0.61	2.0	300	6.0	900	80	3.2	0,15
3/8"	- 6	9,5	0.37	17,5	0.69	2.0	300	6.0	900	100	3.9	0,16
1/2"	- 8	12,7	0.50	22,0	0.87	2.0	300	6.0	900	125	4.9	0,24
5/8"	- 10	15,9	0.63	26,5	1.04	2.0	300	6.0	900	160	6.3	0,27
3/4"	- 12	19,1	0.75	29,4	1.16	2.0	300	6.0	900	190	7.5	0,40
1"	- 16	25,4	1.00	36,2	1.43	2.0	300	6.0	900	254	10.0	0,55

On dash size - 3 (3/16") the outer tube is smooth cover