

**BACRUFLEX**Al servicio de la minería,  
pesquería e industria

Catálogo de productos

**MANGUERAS  
HIDRÁULICAS****MANGUERA SUCCION AGUA TRANSP. NARANJA**PVC virgen c/ PVC rígido - *Tecnología brasilera*

-10°C a +65°C

**Construction****Wall:** High quality plasticized PVC**Reinforcement:** Rigid PVC helix**PRESION DE TRABAJO 4 BAR****Application**

Very ideally for conveying water, oil, and powder, abrasive mineral sands, gravel, cement, chips, shavings, construction, agriculture and industrial service applications.

**Coupling:** Camlock coupling and clamps are available separately or assembly with hose**Temperature range:** -10°C to +65°C ( 14°F to 150°F )

SPEC.		THICKNESS	WEIGHT	LENGTH	Packing Dimension
inches	1.Dx0.D		M		
3/4"	19x25	3	KGS	m	DXH (M)
1"	25X32	3	0.28	50	0.6*0.28
1-1/2"	38x46	3.5	0.35	50	0.6*0.32
2"	50X58	4	0.6	50	0.7*0.3
2-1/2"	63X72	4.5	0.93	50	1.0*0.18
3"	75X85	5	1.2	50	1.1*0.22
4"	102X114	6	1.7	50	1.3*0.25
6"	152x168	8	2.85	50	2.0*0.22
8"	200X222	11	5.5	20	2.3*0.35
10"	250X276	13	10.3	10	0.23*0.23*10
			15.5	10	0.28*0.28*10