



CNG - ELETRICALY CONDUCTIVE

CNG Dispenser Very High Pressure Hose



- Inner tube:** internal core in polyamide
Reinforcement: 1 high tensile steel braid and 1 aramidic fiber braid
Outer tube: red pin-pricked polyurethane
Safety factor: 4: 1
Application: CNG (compressed natural gas) dispenser at very high pressure
Temperature range: - 40°C (- 40°F) + 100°C (+ 212°F)
Couplings: crimped **CNG coupling serie**

Ø nom	dash size	Ø internal		Ø external		working pressure		min. burst pressure		min. bend radius		weight
		mm	inch	mm	inch	MPa	PSI	MPa	PSI	mm	inch	kg/m
1/4"	- 4	6,4	0.25	14.0	0.55	69.0	10000	276.0	40000	40	1.6	0,24
3/8"	- 6	9,5	0.37	18.0	0.71	50.0	7250	200.0	29000	60	2.4	0,26

Construction characteristics and dimensions may be changed at any time without prior notice.

The data contained herein is information purposes only and does not enlarge, amend or imply any warranty other than provided by the manufacturer with the product. Any use of the product not in conformance with the manufacturer's instructions may be dangerous.

Only items in this catalogue are carried in stock. Some items are subjected to minimum quantities or sold only in multiples of standard quantities. Please refer to the price list or contact our commercial department.